




strip⁺tec™ ST




Installation for self-adhesive version:

- 1) Check if support is sound, smooth, clean, dry and free from grease and loose materials.
- 2) Cut profile to the required length and remove the protective film.
- 3) Press downwards on the profile until it is fixed firmly. Do not hammer.


Installation for pre-drilled version:

- 1) Cut profile to the required length and place the mark on the surface of the profile pre-drilled holes.
- 2) Insert and fix the flare head screws.

STRIPTEC profile is generally fixed to link two adjacent floors of similar or different height and covering materials. The rounded shape of this strip profile grants to maximum height difference of 5 mm. To apply STRIPTEC means also to cover up the slight imperfections which may occur during the laying job. It can also be used as a terminal profile provided that the thickness of the surface material does not exceed 5 mm.



Self-adhesive



Drilled

Illustrated scale dimension 1:1



STRIPTEC ST-OL* Brass polished

A laminate polished brass flat bar which is resistant to light mechanical and chemical impacts and lasting wear. The brass article allows an extremely elegant decorative finish to homes and is available in pre-drilled or self adhesive versions.

Available also in the heavy duty version, thickness 1,3 mm, Code STP 30 OLA/OLF.

	B=mm	Art.	Adhesive	Drilled	Not drill.
Material:	18	ST 18	OLA	-	OLN
Laminated Brass	30	ST 30	OLA	OLF	
Finish: Polished (OL*)	35	ST 35	OLA	OLF	
Length: 2,70 metres					
△: 0,90 / 1,35 metres					
Width: 18, 30, 35 mm					

STRIPTEC ST-IL* Polished Stainless Steel

Stainless steel profile with a high resistance to wear and a good resistance to atmospheric agents.

Available in self-adhesive (OLA), drilled (OLF), pre-drilled (OLN) versions.

	B=mm	Art.	Adhesive	Drilled	Not drill.
Material:	18	ST 18	ILA	-	ILN
Stainless Steel	30	ST 30	ILA	ILF	
Finish: Polished (IL*)	35	ST 35	ILA	ILF	
Length: 2,70 metres					
△: 0,90 / 1,35 metres					
Width: 18, 30, 35 mm					

STRIPTEC ST-A* Anodised Aluminium

Full aluminium anodised profile available in Silver (AS), Gold (AO), Bronze (AB) finishes. This product confers to chromatic combination with indoor decoration with all floor covering materials.

	B=mm	Art.	Adhesive	Drilled	Not drill.
Material:	18	ST 18	A*A	A*F	
Extruded anodised aluminium	30	ST 30	A*A	A*F	
Finish*: Silver (AS*), Gold (AO*), Bronze (AB*)	35	ST 35	A*A	A*F	
	40	ST 40	A*A	A*F	
Length: 2,70 metres					
△: 0,90 / 1,35 metres					
Width: 18, 30, 35, 40 mm					

STRIPTEC ST 30* Aluminium Wood Cladding Finish

Profile with to melamine wood tone in 8 different varieties. Good tolerance to abrasion comparable to most melamine coverings.

The melamine embossing on the aluminium is particularly smooth therefore it remains quite clean and blends well with the flooring tone.

	Finish	Adhesive	Drilled
Material:	Whitened	ST 30 RSA	ST 30 RSF
Extruded Aluminium Laminate cov.	Maple	ST 30 ACA	ST 30 ACF
	Beech	ST 30 FAA	ST 30 FAF
	Oak	ST 30 ROA	ST 30 ROF
	Cherry	ST 30 CIA	ST 30 CIF
	Light walnut	ST 30 NCA	ST 30 NCF
	Dark walnut	ST 30 NSA	ST 30 NSF
	Wengé	ST 30 WEA	ST 30 WEF
Length: 2,70 metres			
Width: 30 mm			

△ Pre-cut length available in SELFLINE kit L= 0,90/1,35 m