



covertec™ EP

**COVERTEC EP** is a profile joining two adjacent surfaces of different floor covering material (cement/ceramic or wood/ceramic or with other resin or vinyl flooring combinations) allowing an invisible movement zone, therefore performs also as to movement joint as well as a decorative finishing trim. It also covers slight imperfections of junctions and cuts for floor separation. Aluminium and brass, vertical dovetail anchorage. Patented.



Stainless Steel section



Brass section

Illustrated scale dimension 1:1  
(EP 100\*)



**COVERTEC EP-O\* Extruded Brass**

This brass profile is developed with prime choice raw material in order to guarantee tolerance and endurance to chemical and mechanical solicitations. It is primarily applied on both indoor and outdoor floors and can bear intense transit areas as well as for detailing elegant residential coverings. Through contact with moisture or corrosive media, brass may oxidize on exposed surfaces. This situation can be easily solved by buffing the product with a conventional polisher to return to its original shine. Available in natural brass (ON) or polished brass (OL).

	H=mm		Art.	
Material:	8	EP	80	ON/OL
Extruded Brass	10	EP	100	ON/OL
Finish*: Natural (ON), Polished (OL)	12,5	EP	125	ON/OL
Length: 2,70 metres				

**COVERTEC EP-IL Polished Stainless Steel AISI 304 - DIN 1.4301**

This stainless steel profile is AISI 304 standard which ensures high tolerance to most of diluted chemicals found in laboratories or strong detergents present in food processing plants, commercial kitchens, slaughter houses, breweries, hospitals, public toilets etc.

Material:	8	EP	80	IL
Stainless Steel AISI 304	10	EP	100	IL
Finish*: Polished (IL)	12,5	EP	125	IL
Length: 2,70 metres				